

BLR/OA(OS.D) External Oil Separator For Screw Compressor

BLR/OA(OS.D)螺杆压缩机用外置油分

General Description:

- ◆ Screw-type oil separators are especially designed for screw compressors.
- ◆ These oil separators are suitable for all HFC-coolers and cooling circuits with R22 application.
- ◆ Products with 4 different volume are manufactured as standard: (BLR/OSD-180x2, BLR/OSD-400x2, BLR/OSD-900x3, BLR/OSD-1300x3).

Connection Parts:

- ◆ We determined Input and Output connections according to volume of products.
- ◆ Rotalock valve connection is used in standard products. (Flare/Flare)
- ◆ Different connection may be used upon request.
- ◆ 7/8" Rotalock Valve is installed at tank output in standard products.
- ◆ We determine models of Sight Glass according to diameter of products.
- ◆ Sight glasses may be decreased and increased up to desired number
- ◆ 2 Sight Glasses are available in standard products.
- ◆ We strongly recommend using Safety Valve in products.
- ◆ There is a Safety Valve connection after certain volume. See technical data table for details.
- ◆ Please, contact us for different Safety Valve connections
- ◆ We strongly recommend using Liquid Level Sensor with products.
- ◆ There is oil level sensor connection in standard products.
- ◆ Connection parts for oil heaters and oil thermostat are available in standard products. Details are given in technical data table.

Note:

- ◆ Our firm manufactures products of any required diameter, length, and properties according to relevant standards.
- ◆ Different colors may be used upon request in number of quantities.
- ◆ Oil Separators are manufactured in accordance with CE 97/23/EC directive.
- ◆ Please, contact us for further details.



描述

- ◆ 螺杆式油分是专门为螺杆式压缩机设计的。
- ◆ 这些油分适用于所有的HFC冷风机和R22冷却系统。
- ◆ 标准产品共有4个不同的容积 (BLR/OA-1954, BLR/OA4188, BLR/OA-07111, BLR/OA-25112)。

产品连接件:

- ◆ 我们根据产品的容积来决定输入和输出接口。
- ◆ 标准产品配有锁定阀接口(Flare/Flare)
- ◆ 可根据要求做不同接口尺寸的产品。
- ◆ 标准产品的出口装有接口为7/8"的锁定接头阀。
- ◆ 我们依据产品直径来决定试液镜的型号。
- ◆ 试液镜可根据要求增减。
- ◆ 通常标准产品装有2个试液镜。
- ◆ 我们强烈建议您同时使用安全阀。
- ◆ 达到一定容积之后,会有一个安全阀接口,详细资料请看参数表
- ◆ 如果需要不同接口尺寸的安全阀,请随时与我们联系。
- ◆ 我们强烈建议同时使用液位传感器。
- ◆ 标配是带有一个油位传感器接口的。
- ◆ 用于油加热器和油控制器的接口部件的详细资料,请看参数表。

注意:

- ◆ 我司可根据客户的合理要求定做不同尺寸的油分。
- ◆ 不同颜色的要求是根据数量而定的。
- ◆ 我们的油分是符合 CE 97/23/EC 标准的。
- ◆ 如需更多的参数,请随时与我联系。